

## 655C CRWLR LOADER

### Specs

<b>MANUFACTURER</b>	<b>John Deere</b>
<b>MODEL</b>	<b>655C CRWLR LOADER</b>
<b>DATE OF SPECIFICATION</b>	Mar-03
<b>ENGINE</b>	
Manufacturer/Model	Liebherr D924T-EA1
Net Horsepower @ Rated rpm	130 (97) @ 2000
# Cylinders and Displacement cu in. (L)	4 - 405 (6.6)
Maximum Torque lb-ft	Not published
<b>ELECTRICAL Volts/Alternator amps</b>	24 / 55
<b>TRANSMISSION</b>	
Type Type	Hydrostatic
Speed Ranges	Infinite
Forward	6.8 (10.9)
Reverse	6.8 (10.9)
<b>FINAL DRIVES</b>	
Gear Reduction	Double reduction w/planetary
<b>STEERING/BRAKES</b>	
Type	Dual-path HS w/o ctr rotation
Clutches	Not applicable
Brakes	Hydrostatic drive
<b>HYDRAULIC SYSTEM</b>	
Pump Type	Variable piston
Pump Flow gpm (L/min.)	41 (155)
System Pressure psi (kPa)	3770 (25980)
<b>UNDERCARRIAGE</b>	
Track Gauge in. (mm)	66" (1680)
Length of Track on Ground in. (mm)	98" (2490)
Std. Grouser in. (mm)	20" (510)
Ground Contact Area sq in. (cm <sup>2</sup> )	3,902 (25180 )
Ground Pressure psi (kPa)	8.7 (59.9)
No. of Track Rollers	6
Track Pitch in.(mm)	6.9" (175)
Track Shoes each side	42
<b>LOADER</b>	
SAE Heaped Capacity cu yd (m <sup>3</sup> )	2.35 (1.80)
Bucket Width in (mm)	96" (2438)
SAE Breakout Force lb(kN)	27,675 (123.10)
SAE Tipping Load lb (kg)	23,086 (10472)
Dump Clearance ft (mm)	9' 3" (2820)
Hinge Pin Height ft (mm)	12' 0" (3660)
Digging Depth in. (mm)	5.2" (132)
Reach @ Maximum Height in. (mm)	42" (1067)
<b>GENERAL DIMENSIONS</b>	
Height w/ROPS ft (mm)	10' 3" (3120)
Length w/Loader Bucket ft (mm)	20' 1" (6120)

Ground Clearance in. (mm)

15.6" (396)

**CAPACITIES CAPACITIES**

Fuel Tank gal (L)

69 (261)

Hydraulic Reservoir gal (L)

34 (129)

**SAE OPERATING WEIGHT lb (kg)**

33,950 (15400)

Specifications are based on published information at the time of publication. Specifications are subject to change without notice.

05/01/2008